




GOODWE
your solar engine



D-NS Series



Dual-MPPT Single-Phase

3.0kW/3.6kW/4.2kW/5.0kW

- Lowest start-up voltage at **120V**
 - Widest voltage range in class of **80** to **550V**
 - **30%** lighter than similar products
 - **20%** Volume optimization
 - Built-in **anti-reverse** function
- | | |
|---|--|
| ☐ IP65 protection class | ☐ Max efficiency of 97.8 % |
| ☐ Integrated DC switch & WiFi | ☐ Multiple monitoring and communication |
| ☐ Up to 10 safety measurements | ☐ 45°C full-load output |

Integrated WiFi Solution
multiple user access and mobile Apps



Good Quality Good Value Good Service GoodWe

Technical Data

GW3000D-NS

GW3600D-NS

GW4200D-NS

GW5000D-NS

DC Input Data

Max. DC power [W]	3900	4680	5460	6500
Nominal DC Power (W)	3300	3960	4600	5500
Max. DC voltage [V]	580	580	580	580
MPPT voltage range [V]	80~550	125~550	125~550	125~550
Starting voltage [V]	120	120	120	120
Max. DC current [A]	11/11	11/11	11/11	11/11
No. of DC connectors	2	2	2	2
No. of MPPTs	2 (can parallel)	2 (can parallel)	2 (can parallel)	2 (can parallel)
DC connector	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol

AC Output Data

Normal AC power [W]	3000	3680	4200	5000*
Max. AC power [W]	3000	3680	4200	5000*
Max. AC current [A]	13.6	16	19	22.8
Normal AC output	50/60Hz; 230Vac		50/60Hz; 230Vac	
AC output range	45~55Hz/55~65Hz; 180~270Vac		45~55Hz/55~65Hz; 180~270Vac	
THDi	<3%		<3%	
Power factor	0.8 leading~0.8 lagging		0.8 leading~0.8 lagging	
Grid connection	Single phase		Single phase	

Efficiency

Max. efficiency	97.8%	97.8%	97.8%	97.8%
Euro efficiency	>97.5%	>97.5%	>97.5%	>97.5%
MPPT adaptation efficiency	99.9%	99.9%	99.9%	99.9%

Protection

Residual current monitoring unit	Integrated	Integrated	Integrated	Integrated
Anti-islanding protection	Integrated	Integrated	Integrated	Integrated
DC switch	Integrated (optional)	Integrated (optional)	Integrated (optional)	Integrated (optional)
AC over current protection	Integrated	Integrated	Integrated	Integrated
Insulation monitoring	Integrated	Integrated	Integrated	Integrated

Certifications & Standards

Grid regulation	VDE-AR-N 4105, EN50438, VDE0126-1-1, AS4777.2&.3, G83/G59	VDE-AR-N 4105, G83/G59, VDE0126-1-1, EN50438, AS4777.2&.3, MEA,PEA	VDE-AR-N 4105, EN50438, VDE0126-1-1, AS4777.2&.3, G83/G59	VDE-AR-N 4105, EN50438, VDE0126-1-1, G83/G59, AS4777.2&.3, MEA, PEA
Safety	IEC62109-1&-2, AS3100			
EMC	IEC/EN 61000-6-1,IEC/EN 61000-6-2,IEC/EN 61000-6-3,IEC/EN 61000-6-4,IEC/EN 61000-3-11, IEC/EN 61000-3-12			

General Data

Dimensions (WxHxD) [mm]	347*432*145	347*432*145	347*432*145	347*432*145
Weight [kg]	14	14	14	14
Mounting	Wall bracket	Wall bracket	Wall bracket	Wall bracket
Ambient temperature range	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)
Relative humidity	0~95%	0~95%	0~95%	0~95%
Max. operating altitude	4000m(>3000m derating)	4000m(>3000m derating)	4000m(>3000m derating)	4000m(>3000m derating)
Protection degree	IP65	IP65	IP65	IP65
Topology	Transformerless	Transformerless	Transformerless	Transformerless
Night power consumption [W]	<1	<1	<1	<1
Cooling	Natural convection	Natural convection	Natural convection	Natural convection
Noise emission [dB]	<25	<25	<25	<25
Display	LCD	LCD	LCD	LCD
Communication	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi
Standard warranty [years]	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)

*Note: 4600W for VDE-AR-N4105